


BREEZE MINI SPLIT SERIES





LIMITLESS SOLUTIONS IN THE AIR CONDITIONING INDUSTRY

www.airomaticcorp.com

13 SEER



- 13 SEER EFFICIENCY
- TURBO COOLING FUNCTION
- STYLISH DESIGN WITH HIDDEN DISPLAY
- GOLDFIN EVAPORATOR & CONDENSER
- 3 M INSTALLATION KIT INCLUDED
- QUIET OPERATION & SLEEP MODE
- ECO-FRIENDLY R410A





360° Three Dimensional Air Delivery

360° air swing design allows air to reach every corner of a room within a wide angle.




Auto-Restart

If the unit stops unexpectedly due to a power cut, the AC unit will automatically restart in the previous mode once power is restored.



Self-Diagnosis

Automatic detection of abnormal operation or components fault codes will be displayed on the indoor unit.




Quiet Air Supply System

Large diameter perfusion fan blades raise and lower the rotation speed according to the temperature of the evaporator, thereby lowering noise levels without reducing airflow or cooling output.



Energy Saving

Automatically reduces cooling power or turns off when you are not around; automatically increases cooling power or turns on when you are around.



Golden Fin Anti-Corrosion Treatment

Provides more strength to prevent corrosion, compared to that of conventional units, also protecting its integrity and services during the time.

AIR O MATIC PRODUCT SPECIFICATION SHEET						
Capacity			Btu/h	12,000	18,000	24,000
Model				AOME12DBRE13	AOME18DBRE13	AOME24DBRE13
Indoor unit	Power supply source		V/Ph/Hz	208-230V~/60Hz	208-230V~/60Hz	208-230V~/60Hz
	Rated Power Consumption	Cooling	KW	1.14	1.67	2.4
	Rated Running Current	Cooling	A	5.00	7.80	11.40
	Max. Input Power		KW	1.45	2.2	2.9
	Max. Input Current		A	7.8	11.5	16
	SEER		W/W	13.00	13.00	13.00
	Refrigerant			R410A	R410A	R410A
	Refrigerant Charged		g	570	840	970
	Max. Discharge Pressure		Mpa	4.15	4.15	4.15
	Max. Suction Pressure		Mpa	1.15	1.15	1.15
	Noise level		dB (A)	52	53	59
	Liquid line/ gas side		Inch	(1/4)/(3/8)	(1/4)/(1/2)	(1/4)/(5/8)
	Connection wiring			(3*1.0)*4M	(3*1.0)*4M	(3*1.0)*4M
	Indoor unit weight (Net)		lbs.	17.6	22	31.9
Outdoor unit weight (Net)		lbs.	54	77	89	
Outdoor unit	Compressor	Brand		GMCC	GMCC	HILY
		Dimension				
	Dimension	Net Dimension	inch	25.98*9.45*19.69	33.86*21.46*12.40	34.65*25.79*12.20
		Packing Dimension	inch	30.71*13.58*22.44	36.22*15.75*24.41	37.20*28.54*17.13
Container Loading 20/40/40HQ			sets	304	208	155

* Specifications are subject to change without notice. * Model numbers, pictures, and specifications of all products are subject to change without further notice.

Follow Us:   

www.airomaticcorp.com

© 2017 Air O Matic Corporation. All Rights Reserved